

SURAKU • Accessibility Criteria

Specifications for planning, construction and maintenance of accessible public areas in streets, parks, gardens and courtyards

6 February 2008

ITEM / CONSTRUCTION: DEMARCATION STRIPS Segregated pedestrian footpaths and cycle paths; demarcation strips at kerbside

ACCESSIBILITY REQUIREMENTS	MEASUREMENTS	ITEMS REQUIRING SPECIAL PLANNING ATTENTION See separate instructions	PLANNING INSTRUCTIONS	COLOURS AND LIGHTING	MAINTENANCE REQUIREMENTS
1 SPECIAL LEVEL OF ACCESSIBILITY Pedestrian street milieus City centre areas with public facilities and services Areas surrounding institutions providing health care and services for the elderly and persons with a disability Areas with a lot of housing targeted at the elderly and persons with a disability Public transport terminals and areas surrounding public bus stops Special sports areas and playgrounds Accessible routes in recreational areas, etc.	200-500 200-500 200-500 200-500	Warning areas Walking surfaces Railings Bollards	Material: setts of split-face small natural stone To avoid misunderstanding, no other paving materials resembling these in colouring, surface pattern or texture are to be used nearby Surfaces that are functionally distinguished (for instance pedestrian footpaths and cycle paths): use of differing materials and colours recommended Demarcation strip (min. width 500 mm) recommended at the kerbside, when the pavement adjoins the carriageway	Colour/contrast distinct from surface (contrast requirement: difference between medium grey and black/white) Minimum lighting category K2, min 10 lux Good lighting; glare-free, even	Surface patterns of demarcation strips to be distinct in all weather conditions Colour contrast to remain distinct
2 BASIC LEVEL OF ACCESSIBILITY	INSTRUCTIONS AS ABOVE Gunning	Walking surfaces Railings Bollards	INSTRUCTIONS AS ABOVE	Colour/contrast distinct from surface (contrast requirement: difference between medium grey and black/white) Street lighting in accordance with functional street classification	Surface patterns of demarcation strips to be distinct in all weather conditions Colour contrast to remain distinct

