

SURAKU • Accessibility Criteria

Specifications for planning, construction and maintenance of accessible public areas in streets, parks, gardens and courtyards

ITEM / CONSTRUCTION: GUTTERS AND GULLIES

ACCESSIBILITY REQUIREMENTS	MEASUREMENTS	ITEMS REQUIRING SPECIAL PLANNING ATTENTION	PLANNING INSTRUCTIONS	COLOURS AND LIG
		See separate instructions		
 SPECIAL LEVEL OF ACCESSIBILITY Pedestrian street milieus City centre areas with public facilities and services Areas surrounding institutions providing health care and services for the elderly and persons with a disability Areas with a lot of housing targeted at the elderly and persons with a disability Public transport terminals and areas surrounding public bus stops Special sports areas and playgrounds Accessible routes in recreational areas, etc. 	Covered gutter, if depth > 20 mm $\leq 10 \text{ mm}$ $\leq 5 \text{mm}$ $\int \frac{10 \text{ mm}}{10 \text{ mm}}$ $\int 10 \text{ $	Walking surfaces Rainwater gullies Guidance paving flags Demarcation strips	Logically positioned in longitudinal direction of streets, thus helping to guide persons who are partially sighted Ice and snow melting system recommended Sufficient number of grate- covered rainwater gullies to prevent puddle formation Easy to clean	Colour or material distin surface
2 BASIC LEVEL OF ACCESSIBILITY	See: KT-02 (General Working Instructions for Municipal Engineering) INSTRUCTIONS AS ABOVE	Walking surfaces Rainwater gullies Demarcation strips	Logically positioned in longitudinal direction of streets, thus helping to guide persons who are partially sighted Sufficient number of grate- covered rainwater gullies to prevent puddle formation Easy to clean	Colour or material disti surface

6 February 2008

7

GHTING MAINTENANCE REQUIREMENTS Keeping gutters open, prevention stinct from of icing, regular cleaning (removal of sand and rubbish) stinct from Keeping gutters open, prevention of icing, regular cleaning (removal of sand and rubbish)

