

## **SURAKU • Accessibility Criteria**

Specifications for planning, construction and maintenance of accessible public areas in streets, parks, gardens and courtyards

6 February 2008

ITEM / CONSTRUCTION: WARNING AREAS

ACCESSIBILITY REQUIREMENTS	MEASUREMENTS	ITEMS REQUIRING SPECIAL PLANNING ATTENTION  See separate instructions	PLANNING INSTRUCTIONS	COLOURS AND LIGHTING	MAINTENANCE REQUIREMENTS
1 SPECIAL LEVEL OF ACCESSIBILITY Pedestrian street milieus City centre areas with public facilities and services Areas surrounding institutions providing health care and services for the elderly and persons with a disability Areas with a lot of housing targeted at the elderly and persons with a disability  Public transport terminals and areas surrounding public bus stops Special sports areas and playgrounds Accessible routes in recreational areas, etc.	Width in direction of travel 1,200 mm, when going to staircase leading directly down; otherwise 600 mm	Kerbstone Outside staircases Ramps Guidance paving flags Demarcation strips Loading islands	Used to warn of edges, platforms, ramps, staircases, pedestrian crossings, etc., in the absence of blister paving flags. Alternative materials: • white natural stone paving flags (bush-hammered or fired) • white sawn stone setts (bush-hammered or fired) • white exposed-aggregate concrete paving flags • white concrete paving flags • white blister paving flags (ice and snow melting system installed in the area) To avoid misunderstanding, no other paving materials resembling these in colouring, surface pattern or texture are to be used nearby	Colour/contrast distinct from surface (minimum contrast requirement: difference between medium grey and black/white)  Minimum lighting category K2, min. 10 lux  Good lighting; glare-free, even	Recognisability of warning pattern must be guaranteed Sufficient colour contrast must be maintained
2 BASIC LEVEL OF ACCESSIBILITY	INSTRUCTIONS AS ABOVE	INSTRUCTIONS AS ABOVE	INSTRUCTIONS AS ABOVE	Street lighting in accordance with functional street classification	INSTRUCTIONS AS ABOVE

