

## **SuRaKu • Accessibility Criteria**

Specifications for planning, construction and maintenance of accessible public areas in streets, parks, gardens and courtyards

30 June 2022

item / construction: Gutters and gullies

Items requiring special planning attention **Colours and lighting Accessibility requirements** Measurements **Planning instructions Maintenance requirements** See also other Suraku tables and sources 1 special level of accessibility Covered gutter, if depth > 20 mm Walking surfaces Logically positioned in Keeping gutters open, prevention visual contrast or material distinct longitudinal direction of streets, of icing, regular cleaning from surface Pedestrian street environments Rainwater gullies ≤10 mm thus helping to guide persons (removal of sand and rubbish) Guidance paving flags City centre areas with public who are partially sighted facilities and services Demarcation strips Ice and snow melting system recommended Environments for facilities for the ≤5mm elderly, disabled, social and Sufficient number of gratehealth services covered rainwater gullies to prevent puddle formation Areas with a lot of housing for ±5mm the elderly and disabled Easy to clean Public transport terminals and areas surrounding public bus stops Exercise and playgrounds that cater to all users Accessible routes, e.g. in recreational areas Open gutter 2 basic level of accessibility **INSTRUCTIONS AS ABOVE** Walking surfaces Logically positioned in visual contrast or material distinct Keeping gutters open, prevention longitudinal direction of streets, of icing, regular cleaning from surface Rainwater gullies (removal of sand and rubbish) thus helping to guide persons Demarcation strips who are partially sighted Sufficient number of gratecovered rainwater gullies to prevent puddle formation Easy to clean