



ITEM / CONSTRUCTION: **RAILINGS**

ACCESSIBILITY REQUIREMENTS	MEASUREMENTS	ITEMS REQUIRING SPECIAL PLANNING ATTENTION	PLANNING INSTRUCTIONS	COLOURS AND LIGHTING	MAINTENANCE REQUIREMENTS
<p><b>1 SPECIAL LEVEL OF ACCESSIBILITY</b></p> <p>Pedestrian street milieus</p> <p>City centre areas with public facilities and services</p> <p>Areas surrounding institutions providing health care and services for the elderly and persons with a disability</p> <p>Areas with a lot of housing targeted at the elderly and persons with a disability</p> <p>Public transport terminals and areas surrounding public bus stops</p> <p>Special sports areas and playgrounds</p> <p>Accessible routes in recreational areas, etc.</p>	<p><b>Protective railing</b></p> <p>1,200 mm, when difference in height &gt; 6,000 mm</p> <p>1,000 mm, when difference in height &gt; 3,000 mm</p> <p>900 mm, when difference in height &gt; 700 mm</p> <p>Height of protective structure 900 mm, when height of railing 1,200 mm; otherwise 700 mm</p>  <p><b>Open railing</b></p> <p>when difference in height &gt; 500 mm, but not &gt; 700 mm</p> <p>Applies also when difference in height is less, if there is a risk of tripping</p> <p>Collision barrier</p> <p>Used as middle handrail in staircases</p> <p>Used to separate pram slope from staircase</p> 	<p>Outside staircases</p> <p>Ramps</p> <p>Handrails</p> <p>Bollards</p>	<p>No sharp edges or components causing risk of collision or of clothes being caught in railing</p> <p>Guiderail, if there is service traffic or other motor traffic at upper level</p> <p>Splash shield if railing in underpass</p> <p>For more details, see: RakMK F2 (Safety specifications for buildings)</p>	<p>Guidance lighting where necessary for persons who are partially sighted</p> <p>Safety colours in areas with motor traffic where necessary</p>	<p>Protection by handrail must be ensured at all times. Good working order must be ensured by temporary arrangements before replacing a damaged handrail.</p> <p>Handrail must be within easy reach, if railing includes handrail. Handrails must be smooth; wooden handrails must be free of splinters</p>
<p><b>2 BASIC LEVEL OF ACCESSIBILITY</b></p>	<p>INSTRUCTIONS AS ABOVE</p> <p>Open railing possible in staircases with less than 3 steps</p>	<p>INSTRUCTIONS AS ABOVE</p>	<p>INSTRUCTIONS AS ABOVE</p>	<p>INSTRUCTIONS AS ABOVE</p>	<p>INSTRUCTIONS AS ABOVE</p>