


ITEM / CONSTRUCTION: **TACTILE MAPS AND INFORMATION SIGNBOARDS**

ACCESSIBILITY REQUIREMENTS	MEASUREMENTS	ITEMS REQUIRING SPECIAL PLANNING ATTENTION	PLANNING INSTRUCTIONS	COLOURS AND LIGHTING	MAINTENANCE REQUIREMENTS
<p>1 SPECIAL LEVEL OF ACCESSIBILITY</p> <p>Pedestrian street milieus</p> <p>City centre areas with public facilities and services</p> <p>Areas surrounding institutions providing health care and services for the elderly and persons with a disability</p> <p>Areas with a lot of housing targeted at the elderly and persons with a disability</p> <p>Public transport terminals and areas surrounding public bus stops</p> <p>Special sports areas and playgrounds</p> <p>Accessible routes in recreational areas, etc.</p>	 <p>RT Building Information Card 09-10884 RT Building Information Card 98-10565</p>	<p>Guidance paving flags</p> <p>Railings (guide railings)</p>	<p>Typeface size 25–40 mm, if access to signboard unobstructed; 70-100 mm, if signboard is looked at from a distance of 1-3 metres</p> <p>To avoid risk of collision, mount signboard on base whose front edge is flush with signboard</p> <p>Recommendation: place tactile information and Braille texts in maps and signboards horizontally at an angle at a height of 900 mm</p> <p>Recommendation: provide overhead covering for signboard</p> <p>Always consult specialists at the Finnish Federation of the Visually Impaired or at Finlands Svenska Synskadade</p>	<p>Sufficient colour contrast; minimum 50% tone difference between text and background, also between signboard and background</p> <p>Best legibility: combination of black and white</p> <p>Minimum lighting category K2</p> <p>Good lighting; glare-free, even, sufficient</p> <p>Lighting where necessary</p>	<p>Free access to signboard (arm's reach)</p> <p>Guidance paving flags must remain readily recognisable</p> <p>Sufficient colour contrast must be maintained</p>
<p>2 BASIC LEVEL OF ACCESSIBILITY</p>					